

GEN²

OTIS

OI-7530-X-X-I WireFree Relayer/Monitor

32 Channel Non-Explosion Proof WireFree Relayer/Monitor

The Otis Instruments OI-7530 Relayer is a 32-Channel Gas Alarm System with 3 Relays that can monitor up to 32 GEN II WireFree Gas Detectors simultaneously. Three relays can be configured to activate up to the full scale reading reported and set to be either latching or non-latching. Housed in a NEMA 4X non-explosion proof enclosure allows for quick, easy installation while maintaining a high level of ruggedness for safety.



Product Features

- 32 Channel GEN II WireFree Relayer
- 12 to 35 VDC Operating Voltage with an Optional AC Power Supply
- Operating Temperature Range of -40°C to +70°C
- Graphical LCD with LED Backlight
- 3 Push-Button Interface (ADD, MENU, SUB) with 3 Corresponding Magnetic, Non-Intrusive Switches
- Radio Options: GEN II 900 MHz or GEN II 2.4 GHz Radio
- 3 Individually Configurable Alarm Set-Points: Three Front Panel ALARM LED Indicators (Red); 3 Dry Contact Relays (4 Amps Maximum per Relay)
- Output Options: Wet Contact DC Fault Terminal, Relay 3 Can Optionally Be Configured as a Fault Relay
- NEMA 4X Fiberglass Non-Explosion Proof Enclosure with Clear Lid
- 1-Year Limited Hardware Warranty



301 S. Texas Avenue
Bryan, Texas 77803
P: 979-776-7700

sales@otisinstruments.com



OI-7530-X-X-I WireFree Relayer/Monitor

32 Channel Non-Explosion Proof WireFree Relayer/Monitor

OI-7530-X-X-I Product Specifications

Product Specifications	
Product Type	32 Channel Gas Relayer
Power Type	WireFree Power
Operating Voltage	12V to 35V DC or 120V AC
Current Draw	275 mA Maximum
Power Supply	3.13A (75W), 85/264V AC to 24V DC (Optional)
RF Connection	External N-Female Radio Frequency (RF) Connector
Customizable Settings	3 Individually-Configurable Alarm Set-Points Per Channel Option to Disable Alarm Relays Latching and Non-Latching Relay Settings
Display Screen	128x64 Resolution Graphical LCD Screen Transflective (Sunlight Readable) with LED Backlight
Interface	3 Push-Buttons (MENU, ADD and SUB)
Tamb Temperature Range	-40°C to +70°C
WireFree (Digital) Input	Up to 32 GEN II WireFree (Digital) Sensor Inputs
Relays	3 Dry-Contact Relays with 4 Amp Replaceable Fuses Fault Terminal
Protection	Power Electromagnetic Interference (EMI) Filter
WireFree Radio Options	GEN II 900 MHz Radio or GEN II 2.4 GHz Radio
Product Compatibility	GEN II WireFree Sensors (OI-6000, OI-6900, OI-6940) GEN II WireFree Transmitters (OI-5900, OI-5950)
Networks	52 Networks (GEN II 900 MHz Radio) 78 Networks (GEN II 2.4 GHz Radio) 255 Addresses per Network
Enclosure Material	NEMA 4X Fiberglass Device Enclosure with Clear Lid
Product Dimensions	9 in. L x 9 in. W x 5 in. H (Max. Dimensions with Attachments)
Total Weight	6.8 lbs.
Hardware Warranty	1-Year, Limited
Part Number Formula	OI-7530-[Radio]-[Power Supply]-I OI-7530-X-X-I

